

## Computational Intelligence

### Unit # 9

Artificial Intelligence Lab, IBA, Karachi

Fall 2014

1

## Swarm Intelligence


- Social Insects work without supervision.
- Their teamwork is largely self-organized, and coordination arises from the different interactions among individuals in the colony.
- Although these interactions might be primitive, taken together they result in efficient solutions to difficult problems.
- The collective behavior that emerges from a group of social insects has been dubbed **Swarm Intelligence**.

Artificial Intelligence Lab, IBA

Spring 2014

2

## Examples



Artificial Intelligence Lab, IBA

Spring 2014

3

## Swarm Intelligence

- There are two popular swarm inspired methods in computational intelligence areas:
  - Ant colony optimization (ACO)
  - Particle swarm optimization (PSO)
- ACO was inspired by the behaviors of ants and has many successful applications in discrete optimization problems.
- The particle swarm concept originated as a simulation of simplified social system. The original intent was to graphically simulate the choreography of bird of a bird flock or fish school. However, it was found that particle swarm model can be used as an optimizer.

Artificial Intelligence Lab, IBA

Spring 2014

4

## MASON Demo

Artificial Intelligence Lab, IBA

Spring 2014

5

## Interesting Facts About Ants (Source: Engelbrecht)

- Ants appeared on earth some 100 million years ago, and have a current total population estimated at  $10^{16}$  individuals.
- It is further estimated that the total weight of ants is in the same order of magnitude as the total weight of human beings.
- Most of these ants are social insects, living in colonies of 30 to millions of individuals.

Artificial Intelligence Lab, IBA, Karachi

Fall 2014

6

## Ant Forging Behavior

- Studies of the foraging behavior of several species of real ants revealed an initial random or chaotic activity pattern in the search for food.
- As soon as a food source is located, activity patterns become more organized with more and more ants following the same path to the food source.
- “Auto-magically”, soon all ants follow the same, shortest path.
- This emergent behavior is a result of a recruitment mechanism whereby ants that have located a food source influence other ants towards the food source.
- The recruitment mechanism differs for different species, and can either be in the form of direct contact, or indirect “communication.”

Artificial Intelligence Lab, IBA, Karachi

Fall 2014

7

## Pheromone

- Most ant species use indirect form of recruitment, where communication is via pheromone trails.
- When an ant locates a food source, it carries a food item to the nest and lays pheromone along the trail.
- Forager ants decide which path to follow based on the pheromone concentrations on the different paths.
- Paths with a larger pheromone concentration have a higher probability of being selected.
- As more ants follow a specific trail, the desirability of that path is reinforced by more pheromone being deposited by the foragers, which attracts more ants to follow that path.
- The collective behavior that results is a form of *autocatalytic behavior*, where *positive feedback about a food path causes that path to be followed* by more and more ants.

Artificial Intelligence Lab, IBA, Karachi

Fall 2014

8

## Working of Ant Colonies

- The colony's efficient behavior emerges from the collective activity of individuals following two very simple rules:
  - Lay pheromone
  - Follow the trails of others



Artificial Intelligence Lab, IBA, Karachi

Fall 2014

## Working of Ant Colonies

- In a simple case, two ants leave the nest at the same time and take different paths to a food source, marking their trail with pheromone.
- The ant that took the shortest path will return first, and this trail will now be marked with twice as much pheromone (from the nest to the food and back) as the path taken by the second ant, which has yet to return.
- Their nest mates will be attracted to the shorter path because of its higher concentration of pheromone.
- As more and more ants take that route, they too lay pheromone, further amplifying the attractiveness of the shorter trail.

Artificial Intelligence Lab, IBA, Karachi

Fall 2014

10

## Working of Ant Colonies

- The more time it takes for an ant to travel down the path and back again, the more time the pheromones have to evaporate.
- A short path, by comparison, gets marched over faster, and thus the pheromone density remains high as it is laid on the path as fast as it can evaporate.
- Pheromone evaporation has also the advantage of avoiding the convergence to a locally optimal solution.
- If there were no evaporation at all, the paths chosen by the first ants would tend to be excessively attractive to the following ones. In that case, the exploration of the solution space would be constrained.

Artificial Intelligence Lab, IBA, Karachi

Fall 2014

11

## Ant System: An Example




Fig. 1. An example with real ants.

a) Ants follow a path between points A and E.

b) An obstacle is introduced; ants can choose to go around it following one of the two different paths with equal probability.

c) On the shorter path more pheromone is laid down.

Artificial Intelligence Lab, IBA, Karachi

Fall 2014

12

## Ant System: An Example




Fig. 2. An example with artificial ants.

- The initial graph with distances.
- At time  $t=0$  there is no trail on the graph edges; therefore, ants choose whether to turn right or left with equal probability.
- At time  $t=1$  trail is stronger on shorter edges, which are therefore, in the average, preferred by ants.

Artificial Intelligence Lab, IBA,  
Karachi

Fall 2014

13

## MASON Demonstration

Artificial Intelligence Lab, IBA, Karachi

Fall 2014

14

## ACO\*

- The first algorithmic models of the foraging behavior of ants, as developed by Marco Dorigo in 1992 (PhD thesis)
- A general-purpose heuristic algorithm which can be used to solve different combinatorial optimization problems.
- Not interested in simulation of ant colonies, but in the use of artificial ant colonies as an optimization tool.
- Major differences with a real (natural) ant:
  - Artificial ants will have some memory
  - They will not be completely blind
  - They will live in an environment where time is discrete

\* The Ant Systems: Optimization by a colony of cooperating agents by Marco Dorigo, Vittorio Maniezzo, and Alberto Coloni

## ACO Algorithm

- Let  $b_i(t)$  ( $i=1, \dots, n$ ) be the number of ants in town  $i$  at time  $t$  and let  $m = \sum [b_i(t)]$  be the total number of ants.
- Each ant is a simple agent with the following characteristics:
  - it chooses the town to go to with a probability that is a function of the town distance and of the amount of trail present on the connecting edge;
  - to force the ant to make legal tours, transitions to already visited towns are disallowed until a tour is completed (this is controlled by a tabu list);
  - when it completes a tour, it lays a substance called *trail* on each edge  $(i,j)$  visited.

Artificial Intelligence Lab, IBA, Karachi

Fall 2014

15

# ACO Algorithm

- Let  $\tau_{ij}(t)$  be the **intensity of trail** on edge  $(i,j)$  at time  $t$ .
- Each ant at time  $t$  chooses the next town, where it will be at time  $t+1$ .
- In  $n$  iterations, each ant completes a tour.
- At this point the trail intensity is updated according to the following formula

$$\tau_{ij}(t+n) = \rho \cdot \tau_{ij}(t) + \Delta\tau_{ij} \quad (1)$$

where

$\rho$  is a coefficient such that  $(1 - \rho)$  represents the evaporation of trail between time  $t$  and  $t+n$ .

# ACO Algorithm

$$\Delta\tau_{ij} = \sum_{k=1}^m \Delta\tau_{ij}^k \quad (2)$$

where  $\Delta\tau_{ij}^k$  is the quantity per unit of length of trail substance (pheromone in real ants) laid on edge  $(i,j)$  by the  $k$ -th ant between time  $t$  and  $t+n$ ; it is given by

$$\Delta\tau_{ij}^k = \begin{cases} \frac{Q}{L_k} & \text{if } k\text{-th ant uses edge } (i,j) \text{ in its tour (between time } t \text{ and } t+n) \\ 0 & \text{otherwise} \end{cases} \quad (3)$$

where  $Q$  is a constant and  $L_k$  is the tour length of the  $k$ -th ant.

- In order to satisfy the constraint that an ant visits all the  $n$  different towns, a data structure, called **tabu list**, is associated with each ant that saves the towns already visited upto time  $t$  and forbids the ant to visit them again before  $n$  iterations (a tour) have been completed.

# ACO Algorithm

- **Visibility**,  $\eta_{ij}$ , is defined as the inverse of the length of the edge  $(i,j)$
- The transition probability from town  $i$  to town  $j$  for the  $k$ <sup>th</sup> ant is defined as

$$p_{ij}^k(t) = \begin{cases} \frac{[\tau_{ij}(t)]^\alpha \cdot [\eta_{ij}]^\beta}{\sum_{k \in \text{allowed}_k} [\tau_{ik}(t)]^\alpha \cdot [\eta_{ik}]^\beta} & \text{if } j \in \text{allowed}_k \\ 0 & \text{otherwise} \end{cases} \quad (4)$$

- $\alpha$  and  $\beta$  are parameters that control the relative importance of trail versus visibility.
- The transition probability is a trade-off between visibility and trail intensity.

# Example

	A	B	C	D	E
A	0	5	2	9	3
B	5	0	8	1	9
C	2	8	0	10	2
D	9	1	10	0	4
E	3	9	2	4	0

- Initial Solutions
  - A C D B E 22
  - B A C D E 21
  - E D B C A 15
  - E B C A D 28
  - A D C E B 30
- Given
  - $\rho = 0.6$ ,
  - $Q = 1$
  - $\alpha = 0.8$
  - $\beta = 0.8$
  - $\tau_{ij} = 0$

## Computing $\tau_{ij}$

	A	B	C	D	E
A	0	(1/21)	(1/22+1/21+1/15+1/28)	(1/28+1/30)	0
B		0	(1/15)	(1/22)	(1/22+1/28+1/30)
C			0	(1/22+1/21+1/30)	(1/30)
D				0	(1/21+1/15)
E					0

- Initial Solutions

- A C D B E 22
- B A C D E 21
- E D B C A 15
- E B C A D 28
- A D C E B 30

Artificial Intelligence Lab, IBA, Karachi

Fall 2014

21

## Computing $\tau_{ij}$ and $\eta_{ij}$

	A	B	C	D	E
A	0.000	0.048	0.195	0.069	0.000
B	0.048	0.000	0.067	0.045	0.115
C	0.195	0.067	0.000	0.126	0.033
D	0.069	0.045	0.126	0.000	0.114
E	0.000	0.115	0.033	0.114	0.000

### $\eta_{ij}$

inverse of the length of the edge (i,j)

	A	B	C	D	E
A	0.00	0.20	0.50	0.11	0.33
B	0.2	0.00	0.13	1.00	0.11
C	0.5	0.13	0.00	0.10	0.50
D	0.11	1.00	0.10	0.00	0.25
E	0.33	0.11	0.50	0.25	0.00

Artificial Intelligence Lab, IBA, Karachi

Fall 2014

22

## Computing Transition Probabilities

$$P_{ij}^k(t) = \begin{cases} \frac{[\tau_{ij}(t)]^\alpha \cdot [\eta_{ij}]^\beta}{\sum_{k \in \text{allowed}_k} [\tau_{ik}(t)]^\alpha \cdot [\eta_{ik}]^\beta} & \text{if } j \in \text{allowed}_k \\ 0 & \text{otherwise} \end{cases} \quad (4)$$

- Numerators only

- $p_{AB}^1 = (0.048)^{0.8} (0.20)^{0.8} = 0.024$
- $p_{AC}^1 = (0.195)^{0.8} (0.5)^{0.8} = 0.156$
- $p_{AD}^1 = (0.069)^{0.8} (0.11)^{0.8} = 0.020$
- $p_{AE}^1 = 0.00$

- After Normalization (dividing by the denominator)

- $p_{AB}^1 = 0.121$
- $p_{AC}^1 = 0.778$
- $p_{AD}^1 = 0.101$

- So Ant 1, starting from node A, would decide about the next node based on these probabilities.
- The process is repeated for the other nodes in the sequence as well.
- All the ants follow this process.

Artificial Intelligence Lab, IBA, Karachi

Fall 2014

23

## Initial Findings of Dorigo and Di Caro

- SACO works well for very simple graphs, with the shortest path being selected most often;
- for larger graphs, performance deteriorates with the algorithm becoming less stable and more sensitive to parameter choices;
- convergence to the shortest path is good for a small number of ants, while too many ants cause non-convergent behavior;
- evaporation becomes more important for more complex graphs. If  $\rho = 0$ , i.e. no evaporation, the algorithm does not converge. If pheromone evaporates too much (a large  $\rho$  is used), the algorithm often converged to sub-optimal solutions for complex problems;
- for smaller  $\alpha$ , the algorithm generally converges to the shortest path. For complex problems, large values of  $\alpha$  result in worse convergence behavior.

Artificial Intelligence Lab, IBA, Karachi

Fall 2014

24

## Observations

- From the studies of the simple ACO algorithm, the importance of the exploration–exploitation trade-off becomes evident.
- Care should be taken to employ mechanisms to ensure that ants do not exploit pheromone concentrations such that the algorithm prematurely stagnates on sub-optimal solutions, but that ants are forced to explore alternative paths.
- ACO has an advantage over evolutionary algorithms from similar problems when the graph may change dynamically; the ant colony algorithm can be run continuously and adapt to changes in real time. This is of interest in network routing and urban transportation systems.